WO 2005/094056 PCT/JP2005/005443 - 24 -

CLAIMS

 A data processing apparatus for processing data for respective pages, comprising:

a data reception unit for receiving at least data of a first format for respective pages;

a data conversion unit for converting the data of the first format into data of a second format;

a page data management unit for managing the data of the first and second formats in first and second page data in association with each other; and

10

15

20

25

a control unit for monitoring a storage state of the data of the first format in a memory, and permitting a predetermined process for the data of the first format in accordance with the storage state.

- 2. The apparatus according to claim 1, wherein said control unit further determines whether or not the data received by said data reception unit is the data of the second format, and wherein when the received data is the data of the second format, a conversion operation of said data conversion unit is stopped.
 - 3. The apparatus according to claim 1 or 2, wherein when said control unit determines that storage of the data of the first format in the memory is complete, said control unit permits said data conversion unit to start a data conversion operation from the first format to the second format.

WO 2005/094056 PCT/JP2005/005443 - 25 -

- 4. The apparatus according to claim 3, wherein said control unit monitors completion of the conversion operation of said data conversion unit and a storage state of the data of the second format in the memory, and permits a predetermined process for the data of the second format in accordance with the storage state.
- 5. The apparatus according to any one of claims 1 to 4, wherein said control unit generates said page data management unit in response to the data reception by said data reception unit.

10

15

- 6. The apparatus according to claim 5, wherein said page data management unit is generated for data of each page received by said data reception unit, and when data including a plurality of pages are received, said page data management unit manages the first and second page data while associating respective pages with each other.
- 7. The apparatus according to any one of claims
 1 to 6, wherein said control unit monitors whether or
 20 not a process execution unit for executing the
 predetermined process issues a request for processing
 the data of the first or second format, and controls
 said page data management unit to manage the
 availability of the request.
- 8. The apparatus according to claim 7, wherein the first format is one of a plurality of data formats including raw data, JBIG data, JPEG data, TIFF data,

WO 2005/094056 PCT/JP2005/005443 - 26 -

and TEXT data, and data of the second format has a JBIG data format.

- 9. A data processing method for processing data for respective pages, comprising:
- a data reception step of receiving at least data of a first format for respective pages;
 - a first page data generation step of generating first page data used to manage the data of the first format;
- a control step of monitoring a storage state of the data of the first format in the memory, and permitting a predetermined process for the data of the first format in accordance with the storage state;
- a data conversion step of converting the data of the first format into data of a second format;
 - a second page data generation step of generating second page data used to manage the data of the second format; and
- a page data management step of managing the data

 of the first and second formats in first and second

 page data in association with each other.

25

10. The method according to claim 9, wherein

in the control step, it is further determined whether or not the data received by said data reception unit is the data of the second format, and

WO 2005/094056 PCT/JP2005/005443

- 27 -

when the received data is the data of the second format, a conversion operation in the data conversion

step is stopped.

15

11. The method according to claim 9 or 10,

5 wherein, in the control step, when it is determined
that storage of the data of the first format in the
memory is complete, a data conversion operation is
permitted to start from the first format to the second
format in the data conversion step.

10 12. The method according to claim 11, further comprising

a process permission step of monitoring completion of the conversion operation in the data conversion step and a storage state of the data of the second format in the memory, and permitting a predetermined process for the data of the second format in accordance with the storage state.

- 13. The method according to any one of claims 9 to 12, further comprising
- a request monitoring step of monitoring whether
 or not a process execution unit for executing the
 predetermined process issues a request for processing
 the data of the first or second format, and controlling
 the first or second page data to manage the
 availability of the request.
 - 14. The method according to claim 13, wherein the first format is one of a plurality of data formats

WO 2005/094056 PCT/JP2005/005443
- 28 -

including raw data, JBIG data, JPEG data, TIFF data, and TEXT data, and data of the second format has a JBIG data format.

- 15. A computer program characterized by making a computer execute a data processing method of any one of claims 9 to 14.
 - 16. A data processing apparatus for processing data for respective pages, comprising:
- a data reception unit for receiving data

 10 including a plurality of pages in a plurality of kinds

 of formats;
 - a format determination unit for determining a data format for a predetermined page of the plurality of pages, and setting the data format as a reception data format;

15

- a data conversion unit for converting data of the reception data format into data of a basic format in the data processing apparatus;
- a page data management unit for supporting and
 generating page data in the reception data format and
 the basic format, and managing the page data in
 association with each other; and

a control unit for monitoring a storage state of
the data of the reception data format in the memory,
and permitting a predetermined process for the data of
the reception data format in accordance with the
storage state.

WO 2005/094056 PCT/JP2005/005443
- 29 -

17. The apparatus according to claim 16, wherein said page data management unit is generated for each page with respect to the data including the plurality of pages, and said page data management units for the respective pages are as sociated with each other to manage the page data of the reception data format and the basic format.

18. The apparatus according to claim 16 or 17, wherein said control unit monitors completion of the conversion operation of said data conversion unit and a storage state of the data of the basic format in the memory, and permits a predetermined process for the data of the basic format in accordance with the storage state.

10

19. The apparatus according to any one of claims
16 to 18, wherein said control unit monitors whether or
not a process execution unit for executing the
predetermined process issues a request for processing
the data of the reception data format or the basic
format, and controls said page data management unit to
manage the availability of the request.